

THE WHITCO

COLD WATER INDUSTRIAL DUTY SERIES

There's still no substitute for quality.



STANDARD FEATURES

- Perfect for blasting away dirt and mud
- Available in electric or gas engines
- Ball bearing pneumatic wheels for portability
- Heavy-duty construction for dependability and durability
- Ideal for hog producers, farms, factories, construction equipment, paint contractors and other general use

Model	4025 GPC	4030 GPC	5030 GPC	4040 GPC	5040 GPC	5050 GPC	8030 GPC
CAPACITY	4 GPM	4 GPM	5 GPM	4 GPM	5 GPM	5 GPM	8 GPM
PRESSURE	2500 PSI	3000 PSI	3000 PSI	4000 PSI	4000 PSI	5000 PSI	3000 PSI
ENGINE/MOTOR	9 HP, Vanguard, Oil Alert, Overhead Valve	16 HP, Vanguard, Oil Alert, Overhead Valve	18 HP, Vanguard, Oil Alert, Overhead Valve	16 HP, Vanguard, Oil Alert, Overhead Valve	18 HP, Vanguard, Oil Alert, Overhead Valve	25 HP, Kohler, Oil Alert, Overhead Valve	25 HP, Kohler, Oil Alert, Overhead Valve
PUMP	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers
HOSE	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	1/2" x 50'
WAND	Trigger	Trigger	Trigger	Trigger	Trigger	Trigger	Trigger
DRIVE	Belt	Belt	Belt	Belt	Belt	Belt	Belt
GAS TANK	2.08 Gallons	2.08 Gallons	4.7 Gallons	4.7 Gallons	4.7 Gallons	5.75 Gallons	5.75 Gallons
WHEELS	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic
DIMENSIONS	L-49" H-35" W-29 1/4"	L-49" H-35" W-29 1/4"	L-49" H-35" W-29 1/4"	L-49" H-35" W-29 1/4"	L-49" H-35" W-29 1/4"	L-49" H-35" W-31 1/4"	L-49" H-35" W-31 1/4"
SHIPPING WEIGHT	325 lbs.	345 lbs.	385 lbs.	375 lbs.	385 lbs.	435 lbs.	435 lbs.

Model	4020 EPC	4030 EPC	5020 EPC	5030 EPC	5040 EPC	5050 EPC	8030 EPC
CAPACITY	3.7 GPM	3.8 GPM	4.8 GPM	5 GPM	5 GPM	5 GPM	8 GPM
PRESSURE	2000 PSI	3000 PSI	2000 PSI	3000 PSI	4000 PSI	5000 PSI	3000 PSI
ENGINE/MOTOR	5 HP, 230 V, 1 PH	8 HP, 230 V, 1 PH	6 HP, 230 V, 1 PH	10 HP, 230 V, 1 PH	15 HP, 230 V, 3 PH	20 HP, 230 V, 3 PH	20 HP, 230 V, 3 PH
PUMP	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers
HOSE	3/8" X 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	1/2" x 50'
WAND	TRIGGER	Trigger	Trigger	Trigger	Trigger	Trigger	Trigger
DRIVE	BELT	Belt	Belt	Belt	Belt	Belt	Belt
DIMENSIONS	L-48 1/2" W-29" H-32 1/2"	L-48 1/2" W-29" H-32 1/2"	L-48 1/2" W-29" H-32 1/2"	L-53" W-33" H-32 1/2"	L-53" W-33" H-32 1/2"	L-53" W-33" H-32 1/2"	L-53" W-33" H-32 1/2"

Whitco
CLEANING SYSTEMS

MEMBER OF
CETA
CLEANING EQUIPMENT TRADE ASSOCIATION